METHOD AND APPARATUS FOR ENCODING AND DECODING AN OBJECT

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The present invention relates to an object encoding and decoding technique. It particularly relates to a method and an apparatus for encoding and decoding an object, that has a surface described as a polygon mesh.

10

2. Description of the Related Art

The widespread use of the Internet gives an opportunity for people to access an enormous amount of information without any special facilities. As this convenience has become understood, electronic commerce using the Internet has developed rapidly. In particular, online shopping in which orders of commodities are made based on published catalogs, has lately drawn public attention as one of the attractive uses of electronic commerce.

20 One of the most important points of online shopping is how to show commodities attractively. To show a photograph of the commodity can be effective for this purpose, but when users want to look at the commodity from different angles, it is hard to meet such a requirement with a 2-dimensional

25 photograph. Therefore, as a recent trend, commodities are

MN-70005

often modeled as polygon data so that the users can freely

manipulate the 3-dimensional model through magnification,

rotation, and the like.

However, when commodities are represented as polygon

5   data, the amount of data required raises problems. The

polygon data required for one commodity could be several

megabytes if designed to show the fine structure of the

commodity. Such large data sizes are difficult to manipulate

and users cannot have the same feeling as when they look at

10   paper catalog pages or the like. The success of online

shopping depends on how quickly commodity image can be

transmitted and displayed and how the image data and 3-

dimensional information can be stored in a limited space of

storage devices.

15

SUMMARY OF THE INVENTION

The present invention has been made in view of the

above-mentioned problems. One of the objects of the invention

20   is to provide a technology for encoding and decoding polygon

mesh data of objects such as commodities. Another object of

the invention is to provide a technology for providing useful

indices for the object at the same time when its polygon data

are compressed. Yet another object of the present invention

is to provide a technology for encoding and decoding the polygon data by which the encoded polygon data can be decoded in a short time. Still another object of the present invention is to provide a technology for properly encoding and decoding the polygon data with a fine structure that may not exist in reality.

According to one aspect of the present invention, an object encoding method is provided. The method comprises obtaining a description of a surface of an object, defining an origin on the surface, decomposing the surface into a plurality of independent shape components according to a distance from the origin to a point of the surface, and encoding the shape components. If the object is described as a polygon mesh, the origin may be a predefined base vertex in the polygon mesh, and the distance may be a graph distance from the base vertex to a vertex of the polygon mesh.

The graph distance may be defined, for example, as the number of edges or the distance along a path from a base vertex to another vertex. In particular, in some cases, such as where the distance is defined as the number of edges, the distance may be represented by a natural number. The shape components may include a contour graph that is a set of edges that connect vertices that have the same graph distance. Roughly speaking, the shape components can be independent

regions each of which is a slice of the object sliced starting from the base vertex. Once the distance, particularly a graph distance, is introduced, the object can be easily decomposed into the shape components uniformly. Furthermore, since each

5 of the shape components is an independent region, it can be easily encoded. The shape components include global topological information of the object. Here, global topological information is intended to exclude local topological information such as connectivity information

10 between polygon vertices. Examples of global topological information are a structural graph or a skeleton structure obtained on the basis of the graph distance. The global topological information is useful as an index of the object for searching purposes.

15   The encoding the shape components may include encoding geometrical information of the object and encoding local topological information of the object. An example of local topological information is connectivity information between polygon vertices. The encoding of the local topological

20 information may include a description indicating that the object is a non-manifold when a shape represented by the polygon mesh is a non-manifold. In this case, the description may describe the number of sets of polygons such as triangles around a vertex that characterizes the non-manifold. The

description may also describe the number of planes around a vertex that characterizes the non-manifold.

The encoding the geometrical information may be adapted to a local size of the polygon mesh. As an example, the difference between a predicted value and a real value of a vertex under consideration may be encoded by an entropy coding. The difference may be adjusted so that the entropy coding can be optimized. The geometrical information may include information relating to color or a normal of a vertex and a plane. In this case, the difference between a predicted value and a real value of such information may be encoded by the entropy coding.

According to another aspect of the present invention, an object decoding method is provided. The decoding method may be used in combination with the object encoding method of the present invention. The method comprises obtaining encoded data which describes a surface of an object, extracting a plurality of independent encoded shape components which are encoded after being decomposed according to a distance from an origin of the surface, which is included in the encoded data, to a point of the surface, and decoding the encoded shape components.

According to still another aspect of the present invention, an object encoding apparatus is provided. The

MN-70005

apparatus embodies the above-mentioned object encoding method and comprises a unit which obtains a description of a surface of an object, a unit which defines an origin on the surface, a unit which decomposes the surface into a plurality of

5 independent shape components according to a distance from the origin to a point of the surface, and a unit which encodes the shape components.

According to still another aspect of the present invention, an object decoding apparatus is provided. The

10 apparatus embodies said object decoding method and can be used in combination with said object encoding apparatus. The apparatus comprises a unit which obtains encoded data which describe a surface of an object, a unit which extracts a plurality of independent encoded shape components which are

15 encoded after being decomposed according to a distance from an origin of the surface, which is included in the encoded data, to a point of the surface, and a unit which decodes the encoded shape components.

According to still another aspect of the present

20 invention, an object encoding method is provided. The method comprises obtaining an object, defining a function relating to a distance on a surface of the object, obtaining a structural graph of the object on a basis of a value of the function, and encoding the object in such a form that the structural graph

MN-70005

is included. The structural graph may be explicitly or implicitly included in the encoded data. The encoded object data may be in such a form that the structural graph can be reconstructed or referred to for a future use. When the

5 object is represented as a polygon mesh, the function may output the number of polygon edges along the path from a predefined base vertex in the polygon mesh to a vertex of the polygon mesh.

Moreover, any arbitrary combination of the above-

10 mentioned structural components in the present invention is still effective as an embodiment when applied as a method, a system, a server, a terminal, a computer program, and so forth.

This summary of the invention does not necessarily

15 describe features that must be included. The invention may also be a sub-combination of these described features.

BRIEF DESCRIPTION OF THE DRAWINGS

20 The above and the other objects, features, and advantages, will become more apparent from the following description of preferred embodiments taken in conjunction with the accompanying drawings wherein:

Fig. 1 shows the relation among indices of

singularities, k-cells, and objects to be coded with them;

Fig. 2a shows one pair of surfaces with the same sequence of Morse indices;

Fig. 2b shows another pair of surfaces with the same

5   sequence of Morse indices;

Fig. 2c shows still another pair of surfaces with the same sequence of Morse indices;

Fig. 3a illustrates the relation between a torus and its critical points;

10   Fig. 3b illustrates the relation between a torus and its cross sectional contours;

Fig. 3c illustrates the relation between a torus and its Reeb graph;

Fig. 4a shows a parent-child relation of contours;

15   Fig. 4b shows a tree structure of contours having a parent-child relation;

Fig. 5 is a diagram explaining a method for encoding a torus using operators;

Fig. 6 shows an example of programming operators in

20   pseudo-Pascal code;

Fig. 7 shows an example of programming operators in pseudo-Pascal code;

Fig. 8 shows an example of programming operators in pseudo-Pascal code;

Fig. 9 shows icons corresponding to cells;

Fig. 10 shows the pasting of cells;

Fig. 11 shows an example of the Reeb graph of an object constructed with icons;

5 Figs. 12(1), 12(2), 12(3), 12(4), 12(5), 12(6), 12(7), 12(8), 12(9), 12(10), 12(11), and 12(12) show the cross sectional contours of an object;

Fig. 13 is a list of operators for constructing an object;

10 Fig. 14 shows a homotopic transformation of contours;

Fig. 15 shows four main parameters of an operator;

Fig. 16 shows gradual transformation of an upper contour into a lower one using a guiding curve;

Fig. 17 shows various types of shape components of an

15 embodiment;

Fig. 18 shows a marching pattern;

Fig. 19 shows a triangle strip of an annulus;

Fig. 20 shows a triangle strip of a 2-cell;

Fig. 21 shows shape components constructed when a single

20 base vertex is specified;

Fig. 22 shows shape components constructed when several base vertices are specified;

Figs. 23(a) to 23(t) show how connectivity information is encoded;

MN-70005

Fig. 24 shows one example of a non-manifold object;

Fig. 25 shows another example of a non-manifold object;

Fig. 26 illustrates how the connectivity information is encoded by using a toroidal graph;

5 Fig. 27 shows a compression method using connectivity prediction;

Fig. 28 is a block diagram showing an object encoding apparatus of the embodiment;

Fig. 29 is a block diagram showing an object decoding 10 apparatus of the embodiment.

DETAILED DESCRIPTION OF THE INVENTION

Although the preferred embodiments of the present 15 invention will be described herein, the true scope of the present invention is broader than that of these preferred embodiments and is more particularly described in the claims. Prior to describing the embodiments, the following "base techniques" are introduced in order to help explain the 20 subject area. These "base techniques" are based on a dissertation given by Dr. Yoshihisa Shinagawa of Tokyo University, in 1993. The full dissertation may be helpful for understanding the present invention.

Base Techniques

[1] Surface Coding Based on Morse Theory

(1) Introduction

The shape of a solid or a surface in 3D space is

5   generally represented as a sequence of symbols for coding.

The coding herein means an object expression using necessary

information for modeling an object. In the case of natural

objects, a shape can have so many degrees of freedom that

coding them demands certain simplification. Topology is a

10 mathematical means for performing such simplifications.

3D objects may be interpreted using Morse theory as a

mathematical tool. As it is described later, the objects can

be modeled very effectively and consistently. However, Morse

theory alone is not sufficient for precise 3D surface coding.

15 The following explains the reasons for this, and describes a

way to solve the problem by developing some effective

extensions to Morse theory.

(2) Classical Morse theory

Morse theory was primarily motivated by the calculus of

20 variations, where the problem is describing the minima of a

functional on an infinite dimensional space of paths.

Conversely, one can also use the minima of a functional to

describe some topological features of spaces that are

otherwise hardly describable. The following is a brief

overview of Morse theory.

1. Differentiable manifolds

The spaces to which Morse theory can be applied are differentiable manifolds. Finite dimensional manifolds will

5 next be considered.

Given an integer n, an n-dimensional manifold is a topological space such that any point has a neighborhood that can be mapped, one-to-one and bicontinuously, on a subset of the n-dimensional space R^n. Such a mapping is called a chart

10 and provides coordinates for the points in its domain, which correspond to latitude and longitude in the case of the globe. For the manifolds to be p times differentiable, the transformation from one coordinate system to another should also be p times differentiable for points in the range of two

15 different charts.

One can thus see a manifold as being made of pieces of R^n overlapping in a differentiable way. For instance, a line and a circle can be given with structures of 1-dimensional manifolds, and the surface of a sphere can be made a 2-

20 manifold using at least two charts. One can make the surface of a torus a 2-manifold using at least four charts. Removing knotted circles from R^3 gives examples of 3-manifolds, and higher dimensional manifolds appear concretely as, for example, configuration spaces of robot arms.

2. Differentiable mapping and singularities

Using charts, mapping from a p-manifold to an n-manifold can be numerically expressed as mapping from pieces of R^p to pieces of R^n. For this mapping, one can check

5 differentiability: A mapping is of class C^k if its components are k times continuously differentiable.

Let's define a height function on coordinates, which returns the height of a given point (such as z-coordinate of an object embedded in 3D-space). Jacobian matrix of a height

10 function h: R^2 -> R is given as

$$J = \begin{pmatrix} \dfrac{\partial h}{\partial x_1} \\ \dfrac{\partial h}{\partial x_2} \end{pmatrix}$$

One can compute a Jacobian matrix at each point. Its rank is at most min(n, p). Points at which the rank of the Jacobian matrix reaches this maximal value are called "regular points",

15 while the others are called "singular points" or "critical points". Singular points concerning the height function include "peak points" ("maxima"), "saddle points" and "pits" ("minima"). In other words, at singular points, the vector of Jacobian matrix becomes zero, and the normal vector is

20 oriented in the same direction as that of height.

3. Hessian matrix and index

For a mapping from an n-manifold to R (we call such mapping

"functions on a manifold"), a point is critical if and only if all partial derivatives are null. At such a point the aforementioned function is thus approximated by a quadratic form based on second order partial derivatives, the matrix of

5 which is called the Hessian matrix, and its components are described as follows:

$$h = \begin{pmatrix} \dfrac{\partial^2 f}{\partial x_1^2} & \dfrac{\partial^2 f}{\partial x_1 \partial x_2} & \cdots & \dfrac{\partial^2 f}{\partial x_1 \partial x_n} \\ \dfrac{\partial^2 f}{\partial x_2 \partial x_1} & \dfrac{\partial^2 f}{\partial x_2^2} & \cdots & \dfrac{\partial^2 f}{\partial x_2 \partial x_n} \\ \cdots & \cdots & \cdots & \cdots \\ \dfrac{\partial^2 f}{\partial x_n \partial x_1} & \dfrac{\partial^2 f}{\partial x_n \partial x_2} & \cdots & \dfrac{\partial^2 f}{\partial x_n^2} \end{pmatrix}$$

The number of negative definite Hessian matrix at the singular point is called the index of the singularity. As

10 shown in Fig. 1, the index is also equal to the number of minus signs in the reduced form. Indices of peak point, saddle point and pit are 2, 1 and 0, respectively. As shown in Figs. 3a-3c, a torus has one, two and one critical points having indices 2, 1 and 0, respectively.

15 A singularity is not degenerate if the Hessian matrix has rank n at that critical point, and it is then called "nondegenerate". Any C^2 function can be approximated by a Morse function. A function on a manifold is called a Morse function if none of the singularities are degenerate.

20 Therefore, the critical points of a Morse function are

isolated, so for a compact manifold, only a finite number of them exist.

4. Homotopy types

Given a manifold and a Morse function on it and knowing the sequence of the indices of that function's singularities, Morse theory shows that a topological space with the same homotopy type as the manifold can be constructed as a cell complex after a sequence of operations corresponding to the singularities of the Morse function.

For any real number representing a height, the cell gives a model for the part of the manifold whose points are below that heights. As R is scanned from top to bottom, the topology of the complex does not change between two successive singular values, but each time a singular value is crossed, the cell complex is updated by attaching a k-cell to the former complex, where k is the index of the singularity. In brief, the shape of an object can be retrieved by attaching cells with the same dimensions as those of critical points.

Fig. 1 shows the relationship among indices of singularities, k-cells and an object to be coded by them. Here, the object is represented by a torus. As shown in Fig. 1, each time the threshold crosses critical heights, the topology of the set of points below the threshold changes. This change is topologically equivalent to attaching a k-cell.

As shown in this Figure, 2-cell (k=2), 1-cell (k=1), and 0-cell (k=0) can be represented by shapes such as a bowl laid upside down, a string, and a single point, respectively. The shape of the original object can be retrieved by attaching

5   those cells together to build a cell complex followed by transforming it as in clay works. For example, a torus can be built by attaching one 2-cell, two 1-cells, and one 0-cell.

Note that the mere sequence of indices does not completely describe the cell complex. Figs. 2a-2c show three

10   pairs of surfaces with the same sequences of Morse indices, respectively. Thus, with the sequence of indices only, the cell complex cannot be completely determined. Therefore, one must know which connected components of the cross section will be involved in attaching each cell.

15   G. Reeb proposed that one can consider a graph obtained from the manifold as a topological quotient space. The Reeb graph is to represent the mutual relationship of singularities and is obtained by representing the object's surface with contour lines and the connected components of each coordinate

20   with a single point. He did this by identifying in the manifold (assumed to be compact) all the points that have the same value under the Morse function and that are in the same connected component as being a corresponding cross section. That is, the connected components of the part of the manifold

situated strictly between two critical levels are thus
represented by separate line segments--the edges of the graph.
Each singularity corresponds to a vertex of the graph. The
Reeb graph can be said to be a graph representing the skeleton

5   of an object.

Figs. 3a-3c show the relationship between a torus and
its Reeb graph. Fig. 3a shows an original torus, Fig. 3b its
cross sections, and Fig. 3c its Reeb graph, respectively.
Disjointed cross-sectional circles on the same plane in Fig.

10 3b correspond to the separate two edges in Fig. 3c.

(3) Limits of the theory

Importantly, using Morse theory in this classical way
permits only the recovery of the manifold's intrinsic
topological properties. The sequence of indices does not code

15 the way the manifold is embedded in space. For instance, you
cannot determine whether an embedded torus is knotted in
space, since both knotted and unknotted configurations can
lead to the same singularities, as shown in Fig. 2b. The
existence of links (shown in Fig. 2c) is another feature

20 overlooked by simple Morse coding.

(4) Extending Morse coding

This section is restricted to the case of surfaces
associated with compact 2-manifolds of class C^2 that are C^2
embedded in 3D space. It is desirable that this Morse

function on the surface is induced by a height function in space. In fact, it is actually sufficient to slightly rotate a C^2 surface to have singularities become nondegenerate, thereby enabling its height function to become Morse.

5   Morse theory also states that between two critical levels, that is, heights of the planes containing critical points, the topological type of the section does not change. Thus, a number of more or less bent cylinders can be used to model the surface between two such levels. Since nonsingular

10 cross sections are made of circles embedded in a plane, the possible nested configuration call for hierarchical and structural coding--grouping plural circles that are contained in the same circle.

Besides information related to the Reeb graph, that is,

15 on how vertices are connected to each other, a proposed extended coding also contains other information in addition to the Morse index--information about the way cylinders are exchanged and turn around each other between two successive critical values.

20 (5) Coding system example

A prototype coding system example will next be explained. This coding system describes a surface by attaching a k-cell and tracking the changes in the hierarchical structure of contours on cross-sectional planes.

Operators are introduced to describe the attachment of cells and code the surface. The iconic representation of cells attached by the operators enables easy understanding of the structure of the surface to be coded. The major advantage of

5 this coding system is that the topological integrity is guaranteed by the resulting code.

1. Contours with parent-child relations

The method for representing the hierarchical structure of contours will next be described. Here, a tree structure is

10 used.

When a contour contains another contour, the former is called the parent contour of the latter and the latter is called the child contour of the former. Figs. 4a and 4b show the parent-child relation of contours and its tree structure

15 representation, respectively. The parent-child relation can be nested, as shown in Fig. 4a. In the following #N represents contour number N. For example, contour Number 1 is abbreviated #1. #1 is the parent contour of #2, which in turn is the parent contour of #4. For convenience, contours that

20 have no parents, such as #1 and #7, are described as the child contours of "virtual contour #0". Therefore, #0 comes to the top of the tree structure.

We define an array parent #[ ] to show the parent of the given contour. In the example above, parent#[1]=0. On the

other hand, the child contours of a contour are listed in an

array children [ ], to which a pointer is contained. For

example, the pointer to the child contours of #3 is contained

in children[3] and the child contours #5 and #6 are

5   represented as

children[3] $\uparrow$ [1] = 5 and children[3] $\uparrow$ [2] = 6.

For convenience, contours having the same parent

contours are called sibling contours. In Fig. 4a, #2 and #3

are sibling contours. The parent's parent contour is called

10   the grandparent contour and the child's child contour is

called grandchild contour. Also, a contour in whose interior

the object exists is called a solid contour and a contour in

whose interior the object does not exist is called a hollow

contour. In Fig. 4a, #1, #4, #5, #6, and #7 are solid

15   contours, while #2 and #3 are hollow contours.

2.   Operators for attaching cells

There are four defined operators: Put_e0, Put_e1_merge,

Put_e1_divide, and Put_e2. These paste the cells. In what

follows, a k-cell is abbreviated to e^k.

20   Construction proceeds from the top to the bottom of an

object. The process ends when it is no longer possible to

attach cells. The contour structure on the cross-sectional

planes is used to represent the status of the surface which

the operators are constructing.

Fig. 5 shows methods for constructing a torus using these operators. In the following, functions of the operators will be described with reference to this Figure.

1. First, Put_e2(0) is used to create a cell e^2 as shown at the top of Fig. 5. The parameter "0" in Put_e2(0) means that #1 is created inside #0, which is the virtual contour. The cross section of this cell is shown under "Sectional Description" of Figure 5. As shown in Figure 5, Put_e2 has the function to create a contour on a cross-sectional plane. All the contours the operators create are numbered in the order in which they are created. The contour created by Put_e2(0) is #1.

The status of a newly created contour is always "enabled" at first. This means that cells can be attached to the contour. We show our iconic representation of the cell e^2 under "Icon" in Fig. 5.

2. A cell e^1 is pasted to e^2 by Put_e1_divide (1, nil, inside). A newly created contour is numbered as #2. The third parameter "inside" indicates that #2 is created as the child contour of parent#[1]=0, which is the virtual contour. The second parameter is the list of child contours to be operated on. In this case, the second parameter is "nil", which indicates that no operation is performed on child contour, consequently, no child contour is to be removed.

3. Another e^1 is pasted to merge #1 and #2 by

Put_e1_merge (1, 2). This operator merges the two contours

designated by the first and second parameters into the first.

Since the contour indicated by the second parameter disappears

5 by merging, the second contour is removed from the list of

child contours of its parent contour. The status of the

second contour is changed from "enabled" to "disabled".

Therefore, no cell can be attached to this contour.

4. Finally, Put_e0 (1) eliminates #1 by pasting e^0. The

10 status of #1 is changed from "enabled" to "disabled". The

icon reflects this change. Note that when a contour is

attached to a cell e^0, all of its child contours, if any, have

to be disabled beforehand.

The cell attaching procedure ends here because no

15 enabled contours remain.

Figs. 6-8 show examples of operator programs in pseudo-

Pascal code. Max_children and Max_contour_number are defined

here as sufficiently large positive integers. They are used

only for memory allocation purposes.

20 In Fig. 6, Number_of_children shows the number of child

contours for each contour. Most_recently_created# shows the

most recently created contour number. Contour_status shows

whether each contour is enabled or disabled. Children gives

the pointer to the array Child_list that contains the list of

the child contours of a given contour. The end of Child_list

is shown by the constant End_of_list. These variables are

initialized as follows:

most_recently_created#:=0;

5   for i:=0 to max_contour_number do

number_of_children[i]:=0;

for i:=1 to max_contour_number do

contour_status[i]:=disabled;

contour_status[0]:=enabled;

10   Thus, the virtual contour here becomes enabled. Next,

create_new_contour creates a new contour, increases most

recently_created#, and initializes its status.

Procedure create_new_contour;

begin

15   most_recently_created#:=most_recently_created#+1;

contour_status[most_recently_created#]:=enabled;

end

In Fig. 7, we define two procedures and three functions

for later use. add_listed_children adds the contours listed

20 in the second parameter, clist, to the list of the child

contours (children[n]↑) of the first parameter.

remove_listed_children removes the contours listed in the

second parameter, clist, from the list of the child contours

(children[n]↑) of the first parameter. These two procedures

also update the array Number_of _children and Parent#.

On the other hand, the function are_children (n, clist)
returns "true" when all the contours in clist are child
contours of #n. Otherwise it returns "false". The function

5   in_list (n, clist) returns "true" when clist includes #n.
Otherwise it returns "false". The function
list_containing_only (n) is defined to make a list containing
only one contour to be fed to the procedures
add_listed_children and remove_listed_children.

10 The four operators Put_e2, Put_e0, Put_e1_divide, and
Put_e1_merge can now be defined. They are shown in Fig. 8.

1. Put_e2 (n) creates a new contour as the child contour
of #n.

2. Put_e0 (n) eliminates #n by attaching e^0. Here,

15 All_successors_disabled (n) returns "true" if and only if all
the successors of #n are disabled.

3. Put_e1_divide (n, clist, inside) divides #n to create
a new contour. The contours listed in clist become the child
contours of the newly created contour. They are removed from

20 the list of the child contours of #r where either #r=#n or
#r=parent#[n] holds. (This depends on whether they have been
the child contours of #n or parent#[n].) Only these two cases
are permitted.

4. Put_e1_merge (c1, c2) merges #c2 into #c1. #c2 is

removed from the list of child contours of parent#[C2]. All the child contours of #c2 become the child contours of parent#[c1] or #c1, depending on whether #c1 is the parent or the sibling contour of #c2. Only these two cases are

5   permitted.

To easily understand the structure of the surface being coded by these operators, we propose a graphic representation of the cells that constitute the Reeb graph of the surface.

The icons depicted in Fig. 9 represent cells. We paste

10   two cells by letting the flat top and the flat bottom of the two coincide. We depict the cells for hollow contours with white icons and cells for solid contours with black icons. For e^1, plural types of icons exist.

Fig. 10 shows the attachment of cells. The icons of

15   child contours are drawn inside of the icons of their parent contours, as shown in this Figure. Mirror images of the icons on the vertical axis are also allowed.

Icons are characteristic in that they preserve the contour structure to which they are attached. For example,

20   when e^1 is attached to the cells as shown in the top half of Fig. 10, the icon preserves the structure of the parent-child relation of the cells to which it is attached.

Dummy icons are inserted where necessary to adjust the height of cells, as shown in the bottom half of Fig. 10.

Because the Reeb graph may not be a planar graph, we can use

the dummy icons to interchange the cells so that e^1 can be

attached to the adjacent cells. e^1 interchanges the cells

together with its inner structure. To preserve the

5 hierarchical contour structure, the dummy icons cannot exceed

the bounds of the parent contour of the contour to which it is

attached or intrude into other contours. For this reason,

only sibling contours can be interchanged using dummy icons.

In summary, Figs. 11-13 illustrate an example of the

10 code for constructing an object using the operators. Fig. 11

shows an example of the Reeb graph of an object using icons.

Figs. 12 (1), 12(2), 12(3), 12(4), 12(5), 12(6), 12(7), 12(8),

12(9), 12(10), 12(11), and 12(12) are the corresponding cross-

sectional contours, and Fig. 13 shows the operators for

15 constructing the object.

[2] Surface construction from codes using operators

(1) Surface generation as a locus of homotopy

In this section, surface is constructed from codes

obtained by the previous method.

20 As was previously stated, the topology of a contour does

not change between critical sections. When scanned from top

to bottom, the shape of a contour changes. This

transformation of a contour can be best represented by the

notion of a homotopy. A homotopy transforms one function to

another.   In what follows, all the contours are to be

represented by shape functions and the transformation are

described by means of homotopies.   The definition of homotopy

is as given below.

5   Definition: Let f, g : X→ Y be maps where X and Y are

topological spaces.   Then "f is homotopic to g" if there

exists a map F: X x I→ Y such that

$$F(x,0) = f(x)$$

and

10        $$F(x,1) = g(x) \text{ for all points } x \in X.$$

Here $I = [0,1] \in R$.   This map F is called "a homotopy from f

to g".   When F is defined by

$$F(x,t) = (1-t)f(x) + tg(x),$$

it is called a straight-line homotopy.   In Fig. 14, homotopic

15   transformation of contours is shown.   In this Figure, the

upper contour is represented by the shape function f and the

lower by g.   The surface generated is the locus of the

homotopy F from f to g.

(2) Elements for implementing operators

20   The operations that generate a surface as shown in Fig.

14 are described as transforming the contours by homotopies.

1. Elements of the operators

The following four main elements of the operators are

described in Fig. 15.

(i) f: $I \rightarrow R^3$ gives the shape of the upper contour

(ii) g: $I \rightarrow R^3$ gives the shape of the lower contour

(iii) F: the homotopy from f to g

(iv) h: the difference in height between the two contours

5 2. Shape functions

The following shape functions f and g are provided.

(i) point: a constant function that always gives the location of a fixed point

(ii) circle: gives the shape of a circle

10 (iii) polygon: gives the shape of a polygon that connects the given vertices

(iv) Bézier: An n-dimensional Bézier curve is written as

$$f(u) = \sum_{i=0}^{n} B_i^n(u) P_i \ (0 \le t \le 1)$$

and specified by an ordered set of n points called the control

15 points $P_i \in R^3$. The control point can be modified by users.

Here, $B_i^n(t)$ is a Bernstein basis function defined by

$$B_i^n(u) = \binom{n}{i} u^i (1-u)^{n-i} .$$

(v) NURBS (Non Uniform Rational B-Spline) curves: The control points of NURBS curves are also defined by users. A NURBS

20 curve is defined by

$$f(u) = \frac{\sum_{i=0}^{n} N_{i,k}(u) w_i P_i}{\sum_{i=0}^{n} N_{i,k}(u) w_i}$$

MN-70005

where w_i is a weight associated with each control point.

$N_{i,k}(t)$ is a piecewise polynomial of degree (k-1) called a B-spline basis function and defined as

$$N_{i,0} = \begin{cases} 1 \ (x_i \leq u < x_{i+1}) \\ 0 \ \text{otherwise} \end{cases}$$

5

$$N_{i,k}(u) = \frac{(u - x_i)N_{i,k-1}(u)}{x_{i+k} - x_i} + \frac{(x_{i+k+1} - u)N_{i+1,k-1}(u)}{x_{i+k+1} - \dot{x}_{i+1}} \ (2 \leq k \leq n+1) \ .$$

NURBS is extensively used in a great number of CAD systems. It can represent a quadric surface accurately and has a local approximation property, that is, if a control point or the weight associated with it is changed, it affects

10 the shape of the surface only in its neighborhood.

3. Homotopy F

As the homotopy F, functions are provided as follows. They output cross sectional contours.

(i) linear: a straight-line homotopy

15 (ii) quadrant:

$$F(x,t) = \text{quadrant}(x,t) = \sqrt{1-t^2}f(x) + \left(1 - \sqrt{1-t^2}\right)g(x)$$

(iii) parabola: $F(x, t) = (1-t^2)f(x) + t^2 g(x)$

(iv) cardinal spline: A cardinal spline interpolates the upper and lower contours. Parameterization can be done

20 automatically using a toroidal graph that indicates the correspondence between the contours.

(v) guiding curve: A contour is transformed by moving a point

of the contour along a guiding curve.   More than one guiding

curve can be attached to a contour.   When a contour is

represented by a Bézier or NURBS curve, the guiding curves may

be attached to the control points and the transformation may

5   be determined by the movement of the control points.   The

movement of a control point where a guiding curve is not

attached can be computed using the guiding curves of its

adjacent control points.

Fig. 16 shows the gradual transformation of the upper

10   contour to the lower one by attaching a guiding curve to a

contour by users.

In any case, surface patches are generated among the

resulting contours using the cardinal spline.

4. Shape functions of contours for the operators

15   The shape functions of contours for the operators are

given in the following.

(i) Put_e2

   f: point

   g: specified by users (default: circle)

20   F: specified by users (default: quadrant)

(ii) Put_e0

   f: the shape function of the contour to which the e^0 is

attached

   g: point

F: specified by users (default: quadrant)

(iii) Put_el_divide and Put_el_merge

For Put_el_divide and Put_el_merge, the path c of e^1 : [0, 1]$\rightarrow R^3$ of e^1 must be determined. In the implementation, the path c is specified by the locations of c(0), c(1/2) and c(1). The path has to be smooth and its tangent vector at c(1/2) has to be parallel to the xy-plane so that c(1/2) becomes the saddle point of the generated surface. The default location of c(1/2) is at

$$c(1/2) = \begin{pmatrix} \dfrac{c(0)_x + c(1)_x}{2} \\ \dfrac{c(0)_y + c(1)_y}{2} \\ c(0)_z - h \end{pmatrix} \quad \text{where}$$

$$c(t) = \begin{pmatrix} c(t)_x \\ c(t)_y \\ c(t)_z \end{pmatrix}.$$

The default path is an arc of an ellipse connecting c(0) and c(1) given by

$$c(t) = \begin{pmatrix} \left(1 - \sqrt{1-(2t)^2}\right)c(0)_x + \sqrt{1-(2t)^2}\,c(1/2)_x \\ \left(1 - \sqrt{1-(2t)^2}\right)c(0)_y + \sqrt{1-(2t)^2}\,c(1/2)_y \\ (1-2t)c(0)_z + 2tc(1/2)_z \end{pmatrix}$$

for $0 \le t \le 1/2$ and

$$c(t) = \begin{pmatrix} \left(1 - \sqrt{1-(2-2t)^2}\right)c(1/2)_x + \sqrt{1-(2-2t)^2}\,c(1)_x \\ \left(1 - \sqrt{1-(2-2t)^2}\right)c(1/2)_y + \sqrt{1-(2-2t)^2}\,c(1)_y \\ (2-2t)c(1/2)_z + (2t-1)c(1)_z \end{pmatrix}$$

for $1/2 \leq t \leq 1$. The projection of the default path to the xy-place is the line segment connecting c(0) and c(1). A parabolic path can easily be provided by substituting $(1-x^2)$ for $(1-x^2)^{1/2}$. The elements for Put_e1_divide and Put_e1_merge

5   are as follows.

·Put_e1_divide

   f: the shape function of the contour to which e^1 is attached

   c: the path of e^1

   c(0) and c(1): specified by s_1 and $s_2 \in [0, 1]$ where

10   $c(0)=f(s_1)$ and $c(1)=f(s_2)$ respectively

   g_1 and g_2 : obtained by dividing the contour along c

·Put_e1_merge

   c: the path of e^1

   f_1 and f_2 : the shape functions of the contours to which e^1

15   is attached

   c(0) and c(1): specified by s_1 and $s_2 \in [0, 1]$ where $c(0)=f_1$ (s_1) and $c(1)=f_2$ (s_2) respectively

   g: obtained by merging the contours along c

      The transformation for Put_e1_divide is performed by

20   transforming the contour using the path of e^1 as the guiding

curve; i.e.,

      $F(s_1, t)=c(t/2)$

and

      $F(s_2, t)=c(1-t/2)$.

On the other hand, the transformation for Put_el_merge

is obtained as

$$F_1(s_1, \ t)=c(t/2)$$

and

5 $\qquad F_2(s_2, \ t)=c(1-t/2).$

Embodiments

The preferred embodiments of the present invention will

next be described in view of the aforementioned base

10 techniques.

Regarding the base technique [1], the Morse theory,

which provides information concerning singular points and

indices only, can show conceptually the type of cells

constituting a solid. According to Morse theory, the 3D shape

15 of an object can be conceptually reconstructed from basic

singular point information, that is, singular points, their

indices, and the sequence of the singular points. However,

Morse theory fails to present a geometrical relationship in

which those cells are to be connected to one another.

20 The Reeb graph helps to resolve this problem of Morse

theory. The Reeb graph shows the connection between the cells

and can provide information regarding the connectivity

relationship between the singular points, which are

represented by nodes of the graph. Thus, by combining Morse

theory with the Reeb graph, the 3D shape of an object can be recognized in a more detailed manner. In a particular example, existing polygon data representing the shape of the object can be obtained, information relating to singular

5   points of the Morse function can be extracted, and then information relating to the connection between the singular points can be obtained. In principle, the shape of the object can then be understood based on the above extracted and obtained information.

10   Next, it is understood that only the structure or the framework of the object can be reconstructed using Morse theory and the Reeb graph. Namely, only overall topological information can be obtained. Therefore, additional geometrical information may be necessary to understand the

15   more precise geometrical shape of the object. For this reason, contour information may also be obtained.

A significant difference between the base techniques and the present embodiment is the Morse function adopted. The base techniques utilize a height function as the Morse

20   function, which returns the value of the z-axis coordinate. On the other hand, the present embodiment adopts a graph distance as the Morse function. This function returns the number of polygon edges on the shortest path that reaches a vertex under consideration from a base vertex that is defined

on the original polygon object. A Reeb graph can also be

determined for this Morse function and can be generated

automatically.

In the base techniques, when a solid is encoded using

5 the techniques in section [1], a surface can be created for it

using the techniques in section [2]. In general, section [1]

utilizes the concept of homotopy type, while section [2]

utilizes the concept of a homotopy function.

According to the techniques in sections [1] and [2],

10 homotopic connection between respective critical sections can

be used to re-create the surface of the solid. This is

because the topology remains the same between critical

sections, and a homotopic connection keeps the topology

unchanged. In other words, the critical sections are the

15 sections of the necessary and sufficient number of divisions

so that the surface of the object can be re-created by a

continuous function like the homotopy function.

A critical section corresponds to a node of the Reeb

graph and the space between the critical sections corresponds

20 to an edge of the graph. The nodes corresponding to cells e^2

and e^0 are topologically two-dimensional cells that are

equivalent to a two-dimensional open disc. Note that the

cells e^2 and e^0 are singular points that are not degenerate in

the base techniques, but in the embodiment a singular surface

may be degenerate.   However such degeneration can be avoided

by providing an offset onto the singular surface.

A real object contains a surface, which is topologically

equivalent to a cylinder, around each edge of the Reeb graph.

5   Each of the edge topologically corresponds to an annulus,

which is a name for a cylinder in topology.   Therefore the

Reeb graph of the object is obtained, and thereby the object

will be decomposed into components including two-dimensional

cells and annuli in the embodiment.   Once a base vertex is

10   defined on the object, the Reeb graph is uniquely determined.

Therefore any object can be decomposed into the components

constantly and automatically.   This is the merit obtained when

the base techniques are utilized.   As described later, since

the two-dimensional cells and annuli are all in the shape of

15   triangle strips, they can be encoded easily.

In the embodiment, an object encoding is divided into

two stages: encoding connection between polygon vertices and

encoding geometrical information of the polygon vertices.

This is because the base techniques aim at the generation of a

20   smooth surface of the object, while the embodiment aims at the

compression of the polygon data.   A graph distance is adopted

as the Morse function because it can be highly compatibly

applied to the polygon data.

First, a general concept used in the embodiment is

explained and procedures of the embodiment are summarized.

Shape components

Fig. 17 illustrates shape components in the embodiment.

Figure 17 shows a three-dimensional object having an "H"

5   shape.

A contour of a cross-section on a closed surface M is

defined as a connected isovalue line when a continuous

function f: M→R is defined on the surface. In the

embodiment, a graph distance from a base vertex is used as the

10   function f. The first shape component is a contour

represented as a graph structure called the c-graph. A c-

graph is composed by sets of nodes and edges, denoted as c-

nodes 10 and c-edges 14, respectively. The vertices on a

single c-graph have the same graph distance from the base

15   vertex. Note that the graph distance is converted into a

height direction in Figure 17 for ease of understanding.

A c-graph can be composed by only a single c-node 10.

In this case, c-node 10 is a peak or a pit that is a singular

point of the Morse function f. If a c-graph is in a loop

20   shape, a single c-node 10 can be provided on the loop for the

sake of convenience and it is considered that there exists a

c-edge 14 having the c-node 10 as an endpoint. Namely, if a

c-graph is a loop, the c-graph has one c-node 10 and one c-

edge 14 in principle.

If a c-graph is in an "8" shape, there exists one c-node 10 at its cross point, which is a saddle singular point. Each of the two loops of the c-graph is a c-edge 14.

In the embodiment can ensure validity as an orientable closed surface can also be ensured. The Euler equation is satisfied in the same way as for a boundary representation:

$$\#(c\text{-node}) - \#(c\text{-edge}) + \#(2\text{-cell}) = 2 - 2g$$

where # denotes the number of elements, and g is the genus of the closed surface. In the case of Fig. 17, the above equation is 6 - 5 + 1 = 2 - 0. Thus, the encoding apparatus of the embodiment ensures that an object is a closed surface and its encoding is valid by using this equation.

Other shape components are an annulus 16 and a 2-cell 18. An annulus has two different c-graphs or parts thereof as its boundaries, and it is topologically equivalent to a cylinder. A 2-cell has only one boundary composed of a c-graph or part thereof, and is equivalent to an open disc topologically.

The 2-cell and the annulus are extracted from the triangle mesh of an original object based on a graph distance so that they can take a form of a triangle strip as described later. A triangle strip is defined as a linear triangle stream stretching in one direction in which connectivity can be represented as a bit stream as shown in Fig. 18. This bit

stream is called a marching pattern. In the Figure, the

marching pattern is "01001011".

The graph distance is defined for each vertex. The

graph distance for a vertex represents the number of edges

5   that compose a shortest path to the vertex from a base vertex

and is calculated using Dijkstra's algorithm. Here, it is

important to note that the difference between a graph distance

value for a vertex and that for an adjacent vertex must be

zero or one. That is, this graph distance function is a

10   continuous function of a positive integer on a surface, and

can therefore be applied to the homotopy model.

The fundamental shape components have been explained so

far. In the embodiment, an open annulus is also defined in

order to handle an open mesh. An open mesh is a mesh that has

15   an open edge, that is, an edge at which a triangle exists on

only one side of the edge. In order to allow for this

situation, the open annulus takes the form of an acyclic

triangle strip, and its initial and terminal edges correspond

to the open edges. This can be compared to the ordinary

20   annulus described above, circular annulus, in which the

triangle strip is circular. Although an open annulus is

topologically equivalent to a disc, the boundaries consist of

two different c-graphs (or parts thereof) as well as a

circular annulus. Whether an annulus is circular or open can

be determined by traversing the triangles in the annulus in one direction from a starting triangle. If the traversing returns to the starting triangle, the annulus is circular, otherwise open. Note that the open annulus is effective for

5 encoding a non-manifold.

Constructing shape components

The first step in extracting the shape components is the classification of each of the triangles, edges, and vertices in a triangle mesh. A triangle in a mesh may be included on a

10 2-cell or on an annulus. If the three vertices of the triangle have the same graph distance value, the triangle is on a 2-cell, otherwise it is on an annulus.

An edge may belong to any of three components; it may be an edge on a c-graph, an edge on a 2-cell, or an edge on an

15 annulus. An edge is classified using the following steps:

Step 1. If the graph distance values of the end vertices of the edge are different, it is on an annulus, otherwise go to step 2.

Step 2. If there is an edge of an annulus among the four

20 adjacent winged edges, it is on a c-graph, otherwise go to step 3.

Step 3. If at least one triangle among the triangles adjacent to the edge has two edges that are already classified as on a 2-cell, it is on a c-graph, otherwise it is on a 2-cell.

A vertex in a mesh corresponds to either a c-node or a vertex on a c-edge. The vertex is classified according to the attributes of the adjacent edges of the vertex. If the number of c-edges incident to the vertex is two, the vertex is on a c-edge, otherwise it corresponds to a c-node.

Step 3 is a necessary condition for a 2-cell to be in a triangle strip shape. If the existing three edges of a triangle were all on a 2-cell, the 2-cell could be branched out at the triangle and it could not be a triangle strip.

Once the elements of the mesh are classified, the annuli, 2-cells, and c-graphs are constructed by grouping the classified triangles, edges and vertices. Thus, edges on a c-graph that are connected compose one c-graph, a triangle and its adjacent triangle on an annulus are integrated into one annulus if they share a common c-edge on an annulus, and so on. The annuli and 2-cells always take the form of triangle strips when constructed in this manner as shown in Fig. 19 and Fig. 20.

The c-graphs can be decomposed to c-nodes and c-edges by using the classification of vertices and edges described above.

The embodiment compresses the topology of a mesh based on a continuous function of the graph distance and the particular function used sometimes has a great influence on

the compression ratio. The function depends on which vertices of the polygon mesh are chosen as the base vertices. The base vertices may be specified by a user or may be set automatically. Such automatic setting can utilize geometrical

5 information. For instance, the vertex whose z-axis value is the maximum or a cusp of the polygon mesh may be automatically set. Global topological information may be also used. For instance, the vertex where a branch occurs may be set as a base vertex. In any cases the graph distance value on the

10 base vertex is zero.

Fig. 21 shows the shape components constructed when one base vertex 20 is specified. Fig. 22 shows the shape components constructed when several base vertices 20 are specified. In both cases a torus is used as the object.

15 In Figs. 21 and 22 the black lines are c-graphs. In this example, the method used for Fig.22 provides twenty percent higher compression than that for Fig. 21. This improvement is because the selection of a continuous function suitable for the structure of the polygon mesh improves a

20 prediction procedure for geometry compression that is described later.

Lossless connectivity compression

The member variables of each shape component are now compressed by Huffman coding and the marching pattern of the

triangle strip, that is, the connectivity information of the

polygon mesh are encoded as a bit stream. In the case of this

compression method, the original marching pattern can be

completely reconstructed by a decoding process and therefore a

5   lossless compression can be realized.

Touma et al. propose another lossless connectivity

compression method in a paper "Triangle Mesh Compression",

Graphics Interface '98 Proceedings, pp.26-34, 1998. The

proposed encoding method is to describe the total number of

10 other vertices connected with one vertex in a predefined

order.

Figs. 23(a) to (t) show the procedure of Touma's

encoding method. In these Figures, the bold lines are called

an active list. The active list partitions the mesh into an

15 "outer" part containing edges not yet encoded, and an "inner"

part containing edges already encoded. The broken lines

indicate edges already encoded.

In this method, a polygon mesh is first input (Fig.

23(a)). Next, a dummy vertex is added and connected to all

20 boundary vertices (Fig. 23(b)). This is because Touma's

method assumes a closed surface. Next an initial triangle is

selected, and a focus vertex, sometimes simply referred to as

a focus, is marked (Fig. 23(c)). Since the number of vertices

connected with this focus is six, a code word "add 6" is

generated. With the focus unmoved, a next vertex is
considered in counter-clockwise order and a code word "add 7"
is generated. Likewise "add 4" is generated for the last
vertex in the selected triangle.

5   Next, the active list is expanded in counter-clockwise
order around the focus (Fig. 23(d)). A code word "add 4" is
generated for a newly added vertex in the expanded active
list. Likewise, "add 8" (Fig. 23(e)), "add 5" (Fig. 23(f)),
and "add 5" (Fig. 23(g)) are generated. All the edges are now

10   encoded for this focus.

The focus is moved on along the active list in counter-
clockwise order (Fig. 23(h)), "add 4" (Fig. 23(i)) and "add 5"
(Fig. 23(j)) are generated. Since the next free edge of the
focus leads to a vertex already in the active list, the active

15   list is split into two separate active lists (Fig. 23(k)). A
code word "split 5" is now generated. Here "split" indicates
the split of the active list, and "5" is an offset indicating
the number of the unencoded edges along the active list in
clockwise order around the focus. The smaller one of the

20   separate active lists is pushed on the stack for future
treatment, and the encoding procedure proceeds with the second
one. The focus is moved on (Fig. 23(l)), and "add 4" (Fig.
23(m)) and "add 4" (Fig. 23 (n)) are generated. The encoding
procedure is completed for the focus. Next, the dummy vertex

is considered and "add dummy 6" is generated (Fig. 23(o)).
The larger active list is completed for encoding and the
smaller active list is popped from the stack (Fig. 23(p)).
For a new vertex in the active list, "add 4" is generated(Fig.

5   23(q)). At this point all the edges are encoded. The focus
is moved on (Fig. 23(r), 23(s)), and then the smaller active
list is completed for encoding (Fig. 23(t)). The resulting
code is "add 6, add 7, add 4, add 4, add 8, add 5, add 5, add
4, add 5, split 5, add 4, add 4, add dummy 6, add 4".

10   In the embodiment, Touma's encoding method may be
applied to each triangle strip. However, Touma's method
cannot deal with a non-manifold. Another representation
method according to the present invention may be used for
encoding a non-manifold. A non-manifold means an open

15   surface, for instance when a single edge of the polygon mesh
is shared by three triangles.

     The method of the present invention represents the
number of triangles around a vertex. A basic representation
looks like "3 (2, 4, 3)". This representation indicates that

20   there are three sets of triangles around the vertex and these
sets are composed of two triangles, four triangles, and three
triangles respectively. In the case of a manifold, there is
only one set of triangles around a vertex and the generated
code is simply "add 6" or the like in Touma's method. On the

other hand, the representation of the present invention allows a non-manifold to be encoded.

Figs. 24 and 25 show a part of the surface of a non-manifold object. As shown in Fig. 24, a polygon fragment 30 exists over a triangle strip 40 that is composed of c-edge 32 and c-edge 34, the graph distance values of which are m and m+1 respectively. In this case, the vertices 36 and 38, at which the fragment 30 and the triangle strip 40 intersect, are defined as new c-nodes. The edge 43 between the vertices 36 and 38 divides the triangle strip 40 into two regions indicated by s and t. The separate triangle strips are treated as open annuli. In the Figure the fragment 30 itself is encoded as an open annulus. The vertices 36 and 38 are c-nodes and each of them has three sets of triangles around it. Therefore the code will take the form of "3 (a, b, c)". As shown in Fig. 25, if a polygon fragment 30 exists in parallel with a triangle strip 40, a new c-node is not provided. Likewise, a code for a vertex 46 will take the form of "3 (a, b, c)".

In the method of this embodiment, Touma's operators such as add and split are not used, but four operators based on shape components are introduced as follows:

NEW_CNODE: Create a new c-node and move a focus to the c-node;

OLD_CNODE: Move to an existing c-node;

NEW_CEDGE: Create a new c-edge and move to the c-edge;

and

OLD_CEDGE: Move to an existing c-edge.

5   The operators "NEW_CNODE" and "NEW_CEDGE" take as an

argument information relating to a set of triangles such as "3

(2, 4, 3)". The operators "OLD_CNODE" and "OLD_CEDGE" take as

an argument the index of the c-node or the c-edge. The non-

manifold is thus encoded by the invented method.

10   Lossy connectivity compression

The connectivity information may also be encoded in a

lossy way. In the embodiment a toroidal graph representation

is introduced to achieve this lossy compression of

connectivity. The toroidal graph was first proposed by Fuchs

15   et al., "Optimal Surface Reconstruction from Planar Contours",

Communications of the ACM, 20(10), pp. 693-702, October, 1977.

This toroidal graph is used to generate a triangle mesh

between two cross-sections.

Fig. 26 illustrates the reconstruction of the surface of

20   an annulus or a 2-cell by constructing a toroidal graph. An

annulus has two boundaries which consist of the vertex arrays

$(P_0, P_1, \ldots, P_{m-1})$ and $(Q_0, Q_1, \ldots, Q_{n-1})$ respectively where

the size of the marching pattern is m + n. In the case of a

regular annulus, $P_0 = P_{m-1}$ and $Q_0 = Q_{n-1}$ hold. In the

embodiment, it is assumed that there are polygon edges

connecting P_0 - Q_0 and P_{m-1} - Q_{n-1}. Then the toroidal graph has

m by n nodes which are denoted $t_{i,j}$ ($0 <= i < m$, $0 <= j < n$) and each

node $t_{i,j}$ in the toroidal graph means the existence of a

5   polygon edge between the vertex P_i and vertex Q_j. Each $t_{i,j}$

has two directional edges to adjacent nodes and the edge ($t_{i,j}$

$\rightarrow$ $t_{i+1,j}$) indicates the triangle consists of (P_i, P_{i+1}, Q_j), and

the edge ($t_{i,j}$ $\rightarrow$ $t_{i,j+1}$) indicates (P_i, Q_{j+1}, Q_j). Each edge can

be assigned a cost calculated based on the area of the

10 triangle or the angle between the adjacent faces. For

instance, a smaller cost may be assigned to a triangle with a

smaller area or a triangle with a smaller angle to a previous

adjacent face.

By constructing the toroidal graph in this way, the

15 reconstruction of a marching pattern can be reduced to the

problem of searching the minimum cost path from $t_{0,0}$ to $t_{m-1,n-1}$.

The minimum cost path can be solved by calculating the minimum

cost of each node in order according to Dijkstra's algorithm:

$t_{1,0}$ $\rightarrow$ $t_{0,1}$ $\rightarrow$ $t_{2,0}$ $\rightarrow$ $t_{1,1}$ $\rightarrow$ $t_{0,2}$ $\rightarrow$ ... $\rightarrow$ $t_{m-1,n-2}$ $\rightarrow$ t_{m-}

20 $_{2,n-1}$ $\rightarrow$ $t_{m-1,n-1}$.

Furthermore, Dr. Shinagawa proposed an extended toroidal

graph theory in the dissertation that was introduced as the

base techniques. His method is as follows:

1. a pair of points that are mutually closest are

detected between two contour lines;

     2. the closest pair are connected by an edge; and

     3. the other corresponding points are obtained by interpolating between the pair of points.

5   Fuchs' method obtains an optimal path in a discrete manner, but Shinagawa's method is a continuous version of Fuchs' method and can alleviate artificial "wrinkles" on the reconstructed surface that often appears in Fuchs' method. The embodiment may use this extended toroidal graph.

10   <u>Geometry compression</u>

     The embodiment compresses vertex coordinates based on an approach proposed in "Geometric compression through topological surgery", ACM Transactions on Graphics, 17(2), pp. 84-115, April, 1998 by Taubin. Generally, the coordinate

15   values are represented as 32bit floating-point numbers. However, since vertices in a triangle mesh exist in only a limited space, this representation is wasteful. Therefore, considering a bounding box surrounding the object, the float value f_i of coordinates of the vertex v_i can be rounded to a

20   fixed length value n_i. The rounded fixed lengths b_x, b_y and b_z are defined for x, y and z coordinates respectively. In experiments, it was found that b_x, b_y, b_z of between 9 and 12 bits are sufficient to maintain the quality of meshes that contain fewer than 100,000 triangles. The embodiment also

employs a prediction scheme to provide further compression of the rounded values of the fixed length integers. In the encoding of a value of a vertex, the error between the original value and the predicted value calculated from the

5   preceding vertices is coded by Huffman encoding which is an entropy coding.

Although the aforementioned method works well and produces a high compression ratio, it does not take adaptivity of the triangle mesh structure into account. When a mesh has

10 fine and coarse triangles, it is called an adaptive mesh. If the fine parts of the adaptive mesh take on importance, the rounding to fixed length integer is made at the expense of the resolution of the fine parts. In this case, the errors between the original and the prediction values in the coarse

15 parts vary widely, and as a result the performance of the Huffman encoding is degraded.

Fig. 27 shows connectivity prediction and compression methods for the adaptive mesh, which are intended to solve the above problem. In Figure 27, n_{i-2}, n_{i-1}, n_i respectively denote

20 positions defined after the real positions of vertices v_{i-2}, v_{i-1}, v_i are rounded. P_i denotes the position of n_i linearly predicted from n_{i-2} and n_{i-1}, and ε_i denotes the error between the predicted P_i and a reference point n_{ri} that is explained later.

The embodiment assigns an allowance range 60 of $2a_i$ to the rounded value n_i of the vertex v_i, that is, the decoded vertex is allowed to take any value in the range $[n_i - a_i, n_i + a_i]$. The range a_i is larger when the vertex v_i is in a coarse part, and is smaller when the vertex v_i is in a fine part.

Thus, the compression of an adaptive mesh is reduced to the problem of how to decide the error ε_i that has as small a Huffman code as possible while satisfying the condition $P_i + \varepsilon_i \in [n_i - a_i, n_i + a_i]$ so that the reference point n_{ri} (being $P_i + \varepsilon_i$) can be within the allowance range 60. In order to solve this problem, a step number s_i based on a_i is defined as follows:

$$s_i = 2^\beta$$

where β is the maximum integer value that does not exceed $\log_2 2a_i$. The step number s_i takes the form of 2^n where n is an integer value and is the largest number below the allowance range $2a_i$. The ε_i is then calculated using the s_i as follows:

$\varepsilon_i = e_i s_i$, where $e_i \in N$ is a unit vector.

Such ε_i values are uniquely determined and the ε_i is then encoded by Huffman encoding. Note that the step number s_i can be regarded as the resolution of each mesh and therefore the Huffman encoding based on all of the steps s_i is equivalent to encoding each value at different resolution. Thus, effective

compression for an adaptive mesh can be achieved.

In the compression of the vertex coordinates, the allowance range parameter a_i is calculated using the normal vector $norm_i$ of the vertex v_i, the minimum value $lmin_i$ of the distances to adjacent vertices, and an adaptive parameter α specified by a user as follows:

$$a_i = (lmin_i/\alpha) \, |norm_i \, e_{x|y|z}|$$

where the parameter a_i is calculated for x, y and z coordinates individually and the $e_{x|y|z}$ denotes the unit vectors at each coordinate.

The adaptive parameter α is greater than zero so that the parameter a_i becomes larger as the α becomes smaller. That is, a small α makes the compression sensitive to the adaptivity of a mesh and provides a high compression ratio but the decoded object is constructed with poorer quality. The normal vector $norm_i$ is used to restrain the vertex from shifting in the normal direction because a normal shift is more perceptible than an orthogonal shift, especially for vertices on a nearly flat surface.

According to our experiments, an adequate value for α is 8 or 16 or more, and for more bumpy mesh data, occasionally a value of about 4 is sufficient. This is because shifts of coordinates in a bumpy mesh are less conspicuous than in a

smooth mesh. Such features of a mesh should be considered

when the adaptive parameter α is decided.

Note that the aforementioned method is only one example

of the ways to obtain the parameter a_i. Furthermore, this

5   adaptive mesh approach can be applied to other geometrical

information such as texture coordinates, normal vectors,

.colors, and reflection property.

Encoding and decoding procedures

The embodiment uses the following input parameters for

10   encoding a mesh and controlling the quality and compression

ratio:

$v = \{v_{i1}, v_{i2}, \ldots \}$: the array of base vertices;

b_x, b_y, b_z: the rounding bit length of each coordinate;

α: the adaptivity parameter.

15   For encoding topology information, the input parameter v

is used. Although the parameter v sometimes affects the

compression ratio, it is usually sufficient to simply specify

an arbitrary vertex. For encoding geometrical information,

the input parameters b_x, b_y, b_z and α (>0) are used.

20   Once the input parameters have been specified, a

triangle mesh is encoded through the following steps:

Step 1: Construction of shape components.

In this step, a base vertex v is specified and a

continuous function relating to graph distance is determined.

MN-70005

Then an object is decomposed into shape components.

Step 2: Geometry compression.

The coordinate values are rounded to b_x, b_y and b_z bits, and then compressed by the adaptive prediction scheme using

5 the parameter α.

Step 3: Topology compression.

The marching patterns are compressed using toroidal graphs.

It is important that the geometry compression is

10 performed before the marching pattern compression because the computation of toroidal graphs depends on the coordinate values of each vertex. In the decoding phase the toroidal graph cannot refer to the original geometry values, but refers to the encoded values only. Therefore it is necessary to use

15 the encoded geometry values in the encoding phase.

The decoding follows the same steps as the encoding process; i.e., (1) decoding the shape components, (2) decoding the geometry values, and (3) decoding the marching patterns.

In order to test the effectiveness of the embodiment,

20 polygon objects of 20 to 900 kilobytes in VRML 1.0 (ASCII form) were processed. In this experiment, the amount of data is reduced by one to two digits while the degradation of the image quality is almost imperceptible. The time required for encoding and decoding was fairly fast, ranging from 0.5 to 100

seconds.   The experiment was performed using an MMX Pentium™

266MHz personal computer with a Linux operating system.   The

connectivity information using the toroidal graph was

compressed into less than one bit.   The number of bits per

5   triangle was less than 0.2 in the best case.

In the embodiment, it is not necessary to wait until the

completion of decoding in order to display an object, since

the decoded parts can be displayed sequentially.   Therefore

the embodiment is suitable for a progressive display.   Now

10   that the general concept and procedures of the embodiment have

been described, the structure of the embodiment is now

explained.

Fig. 28 shows the structure of an object encoding

apparatus 100 according to an embodiment of the invention.   An

15   object obtaining unit 104 receives the polygon mesh of an

object from a polygon object storage 102, which may be local

storage or on a network or the like.   A function setting unit

106 sets a function relating to a graph distance on a surface

defined by the input polygon mesh.   The function setting unit

20   106 includes an origin defining unit 108 that defines a base

vertex (or base vertices) as a starting point or an origin

from which the graph distance is defined, and a distance

calculating unit 110 that calculates a graph distance from the

base vertex to each vertex on the polygon mesh.

A shape component decomposing unit 112 decomposes the polygon mesh into its shape components, and an encoding unit 114 encodes each of the shape components. Since the function relating to the graph distance can be regarded as a Morse function described in the base techniques above, the encoded data of each shape component includes global structure or topology information of the object in the form of a Reeb graph. The encoding unit 114 includes a geometry compression unit 116 that compresses and encodes the geometry information of the polygon mesh, and a topology compression unit 118 that compresses the connectivity information of the polygon vertices. An encoded data output unit 120 outputs the encoded data to an encoded data storage 122, which may be local storage or on a network or the like.

Fig. 29 shows the structure of an object decoding apparatus 200 according to the embodiment. An encoded data obtaining unit 202 receives the encoded data of an object from an encoded data storage 122, which may be local storage or on a network or the like. A shape component extracting unit 204 extracts the shape components of the object from the input encoded data. A decoding unit 206 decodes each of the extracted shape components. The decoding unit 206 includes a geometry decoding unit 208 that reconstructs the geometry information of the polygon mesh, and a topology decoding unit

210 that reconstructs the connectivity information of the polygon vertices. A decoded data output unit 212 outputs the decoded data to a decoded data storage 214, which may be local storage or on a network or the like.

5   The encoding and decoding procedures performed by the elements in the above configuration have been described herein. Note that the encoding and decoding procedures of the present invention can also be recorded as a computer program and stored in various storage media for distribution, or such
10 a program can be provided via various transmission methods.

For the object encoding and decoding of the embodiment, various modifications can be applied. First, the embodiment assumes that an object is represented in a polygon mesh but this is not intended to be a restriction. For instance, the
15 object may also be represented as a free surface or represented analytically. The object may also be represented using a boundary representation method or represented in constructive solid geometry (CSG). The present invention can also be applied to such object representations. In these
20 cases, a starting point is provided on the surface of the object and the function is defined on the surface. The shape components can also be generated based on the function values and encoded.

Secondly, in the embodiment, the starting point or the

origin is provided on the surface of the object, but the

origin may also be taken from outside or inside of the object.

In this case, a distance from the origin to each point can be

adopted for the function instead of a graph distance.

5   Note also that each of the elements of the procedures

and of the encoding apparatus and decoding apparatus discribed

above may be realized by software and/or hardware.

Although the present invention has been described by way

of exemplary embodiments, it should be understood that those

10   skilled in the art might make many changes and substitutions

without departing from the spirit and the scope of the present

invention that is defined by the appended claims.